

4-way blow ceiling mounted cassette

FWF-BT/BF



AC fan motor unit for ceiling mounting.
Possibility to shut 1 or 2 flaps

- › Modern style decoration panel in white (RAL9010)
- › Compact casing enables unit to fit flush into ceilings and match standard architectural modules
- › Standard drain pump with 750mm lift
- › Comfortable horizontal auto swing ensures draughtfree operation and prevents ceiling soiling
- › Fresh air intake integrated in the same system thus reducing installation cost as no additional ventilation is required


FWF-BT/BF



FWF-BT/BF				02	03	04	05	02	03	04	05
				2-pipe				4-pipe			
Cooling capacity	Total capacity	Super high	kW	2.0	3.2	4.2	5.2	2.0	2.7	3.5	4.5
		High	kW	1.7	2.8	3.3	4.0	1.7	2.3	2.8	3.5
		Low	kW	1.5	2.5	2.9	1.4	1.8	2.6		
	Sensible capacity	Super high	kW	1.5	2.0	2.8	3.5	1.5	1.7	2.4	3.3
		High	kW	1.3	1.7	2.1	2.7	1.3	1.7	2.3	
		Low	kW	1.1	1.4	1.8	1.1	1.0	1.5		
Heating capacity	2-Pipe	Super high	kW	2.9	4.0	5.4	6.7	-	-	-	-
		High	kW	2.6	3.4	4.1	5.3	-	-	-	-
		Low	kW	2.3	2.8	3.6	-	-	-	-	-
	4-Pipe	Super high	kW	-	-	-	-	3.9	3.8	4.9	6.1
		High	kW	-	-	-	-	3.1	3.3	3.9	4.8
		Low	kW	-	-	-	-	2.3	2.8	3.5	
Power input	Super high	W	74	90	118	74	94	121			
	High	W	67	70	89	67	62	74	93		
	Low	W	60	55	62	60	55	66			
Dimensions	Unit	Height	mm	285							
		Width	mm	575							
		Depth	mm	575							
Weight	Unit	kg	19				20				
		Type	Turbo fan								
		Quantity	1								
Fan	Air flow rate	High	m³/h	468	660	876	468	438	618	822	
		Low	m³/h	318	420	318	300	390			
Sound power level	Super high	dB(A)	44	50	55	44	46	52	57		
	High	dB(A)	40	44	49	40	42	46	51		
Sound pressure level	Super high	dB(A)	31	40	45	31	33	42	47		
	High	dB(A)	27	33	39	27	29	35	41		
Piping connections	Drain	OD	mm	VP20 (External dia.26 / Internal dia. 20)							
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-440								
Control systems	Infrared remote control	BRC7E530 / BRC7E531									
	Wired remote control	BRC315D7									

(1) Cooling: entering evaporator water temp. 12°C; leaving evaporator water temp. 7°C; ambient air temp. 35°C; full load operation.

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-484 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.